

# Sorting

Data Structures and Algorithms for Computational Linguistics III  
(ISCL-BA-07)

Çağrı Çöltekin

`ccoltekin@sfs.uni-tuebingen.de`

University of Tübingen  
Seminar für Sprachwissenschaft

Winter Semester 2024/25

# Why study sorting

- Sorting is one of the most studied (and common) problems in computing
- It is important to understand strengths and weaknesses of algorithms for sorting
- Many problems look like sorting. Learning sorting algorithms will help you solve other problems
- Available implementations are highly optimized (we are not just talking about asymptotic performance guarantees)
- In some (rare) cases, implementing your own sorting algorithm may be beneficial

# Bubble sort

- We start with an ‘educational’ sorting algorithm
- Bubble sort is easy to understand, but performs bad – not used in practice
- We start from bubble sort, and see the improvements over it
- The idea is simple:
  - compare first two elements, swap if not in order
  - shift and compare the next two elements, again swap if needed
  - when you reach to the end, repeat the process from the beginning unless there were no swaps in the last iteration

# Bubble sort

## demonstration

89	67	88	12	72	76	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

89	67	88	12	72	76	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	89	88	12	72	76	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	89	12	72	76	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	89	72	76	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	72	89	76	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	72	76	89	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	72	76	89	93	57
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	72	76	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	72	76	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	72	76	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	88	12	72	76	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	12	88	72	76	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	12	72	88	76	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	12	72	76	88	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	12	72	76	88	89	57	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	12	72	76	88	57	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

67	12	72	76	88	57	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	88	57	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	88	57	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	88	57	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	88	57	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	57	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	57	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	57	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	57	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	57	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	76	57	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	57	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	57	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	57	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	57	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	57	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	72	57	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	57	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	57	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	57	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	57	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	57	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	67	57	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## demonstration

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## summary

- Worst case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Average case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Best case:  $O(n)$   
 $O(n)$  comparisons,  $O(1)$  swaps
- Space complexity:  $O(1)$

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## summary

- Worst case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Average case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Best case:  $O(n)$   
 $O(n)$  comparisons,  $O(1)$  swaps
- Space complexity:  $O(1)$
- There are more concerns than performance
  - Many swaps
  - Bubble sort is *in-place*

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## summary

- Worst case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Average case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Best case:  $O(n)$   
 $O(n)$  comparisons,  $O(1)$  swaps
- Space complexity:  $O(1)$
- There are more concerns than performance
  - Many swaps
  - Bubble sort is *in-place*
- The repetitive algorithm pattern is common

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```

# Bubble sort

## summary

- Worst case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Average case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Best case:  $O(n)$   
 $O(n)$  comparisons,  $O(1)$  swaps
- Space complexity:  $O(1)$
- There are more concerns than performance
  - Many swaps
  - Bubble sort is *in-place*
- The repetitive algorithm pattern is common

```
swapped = True
n = len(seq)
while swapped:
    swapped = False
    for i in range(n - 1):
        if seq[i] > seq[i + 1]:
            seq[i], seq[i + 1] \
                = seq[i + 1], seq[i]
            swapped = True
```


- Not practical – it is not used in practice

# Insertion sort

- Insertion sort is one of the simpler sorting algorithms
- It is easy to understand, and reasonably fast for sorting short sequences
- On longer sequences, it performs worse than more advanced algorithms, like merge sort or quicksort (we will study those later)
- The general idea simple:
  - assume the elements arrive one by one, and we have a sorted sequence
  - insert the element to the correct position:
    - shift all elements larger than the new one to the right
    - place the new element in its correct place

# Insertion sort

## demonstration 1




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort

## demonstration 2




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort

## demonstration 3




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort


## demonstration 4



```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort

## demonstration 5




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort

## demonstration 6




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort


## demonstration 7



```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort

## demonstration 8




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1,i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort

## demonstration 9




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort


## demonstration 10



```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort


## demonstration 11



```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort

## demonstration 12




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort


## demonstration 13



```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort

## demonstration 14




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort

## demonstration 15




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort


## demonstration 16



```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort


## demonstration 17



```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort

## demonstration 18




```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
  
```

# Insertion sort

## demonstration 19



```

for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur

```

# Insertion sort

## demonstration 20

12	57	67	72	76	88	89	93
----	----	----	----	----	----	----	----

*sorted*

```
for i in range(1, len(seq)):
    cur = seq[i]
    j = i
    while seq[j - 1] > cur\
           and j in range(1, i+1):
        seq[j] = seq[j - 1]
        j -= 1
    seq[j] = cur
```

# Insertion sort

## performance

- Worst case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Average case:  $O(n^2)$   
 $O(n^2)$  comparisons,  $O(n^2)$  swaps
- Best case:  $O(n)$   
 $O(n)$  comparisons,  $O(1)$  swaps
- Space complexity:  $O(1)$
- In practice, insertion sort is faster than the bubble sort (and also selection sort)

```
for i in range(1, len(seq)):  
    cur = seq[k]  
    j = i  
    while seq[j - 1] > cur\  
        and j in range(1, i+1):  
        seq[j] = seq[j - 1]  
        j -= 1  
    seq[j] = cur
```

# Insertion sort

## summary

- Insertion sort is simple
- It is efficient for short sequences
- For long sequences it is much worse than more advanced algorithms like merge sort or quicksort (coming next)
- It is in-place
- It is *online*: it can sort items as they arrive
- It is *stable*: it does not swap elements with equal keys
- It is *adaptive*: faster if order of elements is closer to the sorted sequence


# Merge sort

## Introduction

- Merge sort is a divide-and-conquer algorithm for sorting
- It is relatively easy to understand (once you get your head around recursion)
- It has good asymptotic performance
- There are many practical cases where merge sort is used
- Basic idea is divide-and-conquer:
  - split the sequence
  - sort the subsequences
  - merge the sorted lists

# Merge sort

## demonstration – divide




# Merge sort

demonstration – combine




# Merge sort

demonstration – combine




# Merge sort

demonstration – combine



# Merge sort

## demonstration – combine



# Merging sequences


```

# s1, s2: sequences to be merged
# s: target sequence
i, j = 0, 0
n = len(s1) + len(s2)
while i + j < n:
    if j == len(s2) or \
        i < len(s1) and s1[i] < s2[j]:
        s[i+j] = s1[i]
        i += 1
    else:
        s[i+j] = s2[j]
        j += 1

```

- Keep two indices on both sequences, starting from the beginning
- Pick the smallest, place it in the target sequence
- The algorithm requires  $O(n)$  steps to complete

# Complexity of the merge sort



# Merge sort

## the implementation

```
def merge_sort(s):  
    n = len(s)  
    if n <= 1: return  
    s1, s2 = s[:n//2], s[n//2:]  
    merge_sort(s1)  
    merge_sort(s2)  
    merge(s1, s2, s)
```

- Once we have `merge()`, the rest is trivial:
  - Split the array into two
  - Recursively sort both sides
  - Stop when the input is length 1

## Merge sort: summary

- Straightforward application of divide-and-conquer
- Worst case  $O(n \log n)$  complexity (best/average cases are the same)
- Merge sort is not in-place: requires  $O(n)$  additional space
- It is particularly useful for settings with low random-access memory, or sequential access
- Merge sort is stable
- It is a well studied algorithm, there are many variants (in-place, non-recursive)


# A short divergence to complexity

the difference between  $O(n^2)$  and  $n \log n$

$n$	$n \log n$	$n^2$
2	2	4
8	24	64
64	384	4096
1K	10 240	1 048 576
1M	20 971 520	1 099 511 627 776
1G	32 212 254 720	1 152 921 504 606 846 976

# A short divergence to complexity

the difference between  $O(n^2)$  and  $n \log n$



# Quicksort

## introduction

- Quicksort is another popular divide-and-conquer sorting algorithm
- The main difference from the merge sort is that big the part of the work is done before splitting
- Its worse time complexity is  $O(n^2)$ , but in practice it performs better than merge sort on average
- General idea: pick a pivot  $p$ , and divide the sequence into three parts as
  - L smaller than the pivot  $p$
  - E equal to the pivot  $p$
  - G larger than the pivot  $p$
- sort L and G recursively
- combination is simple concatenation

# Quicksort

## demonstration – divide


89	67	88	12	57	76	93	72
----	----	----	----	----	----	----	----

At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide




At each divide step

- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations

# Quicksort

## demonstration – divide



At each divide step


- Pick a **pivot**
- Recursively call quicksort twice
  - L for items less than the pivot
  - G for items greater than the pivot
- $O(n)$  operations





# Quicksort

## demonstration – combine




At each combine step:

- Simply concatenate
  - L the sorted items less than  $p$
  - E items equal to  $p$
  - G the sorted items greater than  $p$
- No need for  $O(n)$  merging

# Quicksort

## demonstration – combine




At each combine step:

- Simply concatenate
  - L the sorted items less than  $p$
  - E items equal to  $p$
  - G the sorted items greater than  $p$
- No need for  $O(n)$  merging

# Quicksort

## demonstration – combine




At each combine step:

- Simply concatenate
  - L the sorted items less than  $p$
  - E items equal to  $p$
  - G the sorted items greater than  $p$
- No need for  $O(n)$  merging

# Quicksort

## demonstration – combine



At each combine step:

- Simply concatenate
  - L the sorted items less than  $p$
  - E items equal to  $p$
  - G the sorted items greater than  $p$
- No need for  $O(n)$  merging

# Quicksort

## Python three-liner implementation


```
def qsort(seq):
    if len(seq) <= 1: return seq
    return qsort([x for x in seq if x < seq[-1]]) \ # < p
        + [x for x in seq if x == seq[-1]] \ # = p
        + qsort([x for x in seq if x > seq[-1]]) \ # > p
```

- Practical implementations are not very different
- Common improvements include
  - in-place sorting
  - selecting the pivot more carefully

# Quicksort

## analysis

- Similar to the merge sort, quicksort performs  $O(n)$  operations at each level in recursion
- The overall complexity is proportional to  $n \times \ell$ , where  $\ell$  is depth of the tree
- The recursion tree of merge sort is balanced, so depth is  $\log n$ .
- For quicksort, we do not have a balanced-tree guarantee
- In the worst case, the depth of the tree can be  $n$ , resulting in  $O(n^2)$  complexity



# Quicksort

## average-case complexity and preventing the worst case

- Worst case of the quicksort is when the input sequence is sorted
- If the input sequence is (approximately) random, the *expected* number of elements in each divide is  $n/2$
- To reduce the probability of worst case, *randomized* quicksort picks the pivot randomly
- Best case happens if we pick the *median* of the sequence as the pivot, but finding median already requires  $O(n \log n)$  (or  $O(n)$ , but not very practical)
- A common approach is picking three values (typically first, middle and last) from the sequence, and selecting the 'median of three' as the pivot

# Quicksort

## summary

- Complexity:  $O(n \log n)$  average,  $O(n^2)$  worst
- Despite its worst-case  $O(n^2)$  complexity, quicksort is faster than merge sort on average (in practice)
- The algorithm can easily be implemented in-place (in-place version is more common)
- Quicksort is not stable
- Quicksort is one of the most-studied algorithms: there are many variants, its properties are well known

## Sorting algorithms so far, and the lower bound

Algorithm	worst	average	best	memory	in-place	stable
Bubble sort	$n^2$	$n^2$	$n$	1	yes	yes
Insertion sort	$n^2$	$n^2$	$n$	1	yes	yes
Merge sort	$n \log n$	$n \log n$	$n \log n$	$n$	no	yes
Quicksort	$n^2$	$n \log n$	$n \log n$	$\log n$	yes	no

## Sorting algorithms so far, and the lower bound

Algorithm	worst	average	best	memory	in-place	stable
Bubble sort	$n^2$	$n^2$	$n$	1	yes	yes
Insertion sort	$n^2$	$n^2$	$n$	1	yes	yes
Merge sort	$n \log n$	$n \log n$	$n \log n$	$n$	no	yes
Quicksort	$n^2$	$n \log n$	$n \log n$	$\log n$	yes	no

- Can we do better than  $O(n \log n)$ ?

## Sorting algorithms so far, and the lower bound

Algorithm	worst	average	best	memory	in-place	stable
Bubble sort	$n^2$	$n^2$	$n$	1	yes	yes
Insertion sort	$n^2$	$n^2$	$n$	1	yes	yes
Merge sort	$n \log n$	$n \log n$	$n \log n$	$n$	no	yes
Quicksort	$n^2$	$n \log n$	$n \log n$	$\log n$	yes	no

- Can we do better than  $O(n \log n)$ ?
- If our sorting algorithms requires comparing individual elements, the answer turns out to be 'no'

## Sorting algorithms so far, and the lower bound

Algorithm	worst	average	best	memory	in-place	stable
Bubble sort	$n^2$	$n^2$	$n$	1	yes	yes
Insertion sort	$n^2$	$n^2$	$n$	1	yes	yes
Merge sort	$n \log n$	$n \log n$	$n \log n$	$n$	no	yes
Quicksort	$n^2$	$n \log n$	$n \log n$	$\log n$	yes	no

- Can we do better than  $O(n \log n)$ ?
- If our sorting algorithms requires comparing individual elements, the answer turns out to be 'no'
- Lower bound of worst-case sorting is  $\Omega(n \log n)$

## Sorting algorithms so far, and the lower bound

Algorithm	worst	average	best	memory	in-place	stable
Bubble sort	$n^2$	$n^2$	$n$	1	yes	yes
Insertion sort	$n^2$	$n^2$	$n$	1	yes	yes
Merge sort	$n \log n$	$n \log n$	$n \log n$	$n$	no	yes
Quicksort	$n^2$	$n \log n$	$n \log n$	$\log n$	yes	no

- Can we do better than  $O(n \log n)$ ?
- If our sorting algorithms requires comparing individual elements, the answer turns out to be 'no'
- Lower bound of worst-case sorting is  $\Omega(n \log n)$
- In some special cases, linear-time complexity is possible

# Bucket sort

## introduction

- Bucket sort puts elements of the input into a pre-defined number of ordered 'buckets'
- Elements in each bucket is sorted (typically using insertion sort)
- We can then retrieve the sorted elements by visiting each bucket
- The bucket sort *does not compare elements* to each other when deciding which bucket to place them in
- In special cases, this results in  $O(n)$  worst-case complexity

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9

10-19

20-29

30-39

40-49

50-59

60-69

70-79

80-89

90-99

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9

10-19

20-29

30-39

40-49

50-59

60-69

70-79

80-89

90-99

89

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9

10-19

20-29

30-39

40-49

50-59

60-69

67

70-79

80-89

89

90-99

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	
20-29	
30-39	
40-49	
50-59	
60-69	67
70-79	
80-89	88 89
90-99	

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	
60-69	67
70-79	
80-89	88 89
90-99	

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	57
60-69	67
70-79	
80-89	88 89
90-99	

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	57
60-69	67
70-79	76
80-89	88 89
90-99	

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	57
60-69	67
70-79	76
80-89	88 89
90-99	93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	57
60-69	67
70-79	72 76
80-89	88 89
90-99	93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	57
60-69	64 67
70-79	72 76
80-89	88 89
90-99	93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	53 57
60-69	64 67
70-79	72 76
80-89	88 89
90-99	93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	53 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	43
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	43
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	92 93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	
30-39	
40-49	43 47
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	92 93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	
10-19	12
20-29	21
30-39	
40-49	43 47
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	92 93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	4
10-19	12
20-29	21
30-39	
40-49	43 47
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	92 93

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	4
10-19	12
20-29	21
30-39	
40-49	43 47
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	92 93

- While placing the elements into the buckets, no comparisons between the keys
- Inside the buckets worst-case  $O(n^2)$  (insertion sort)
- What if we had as many buckets as the keys?

# Bucket sort

## demonstration

89	67	88	12	57	76	93	72	64	53	89	54	43	92	47	21	4
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	---

0-9	4
10-19	12
20-29	21
30-39	
40-49	43 47
50-59	53 54 57
60-69	64 67
70-79	72 76
80-89	88 89 89
90-99	92 93

- While placing the elements into the buckets, no comparisons between the keys
- Inside the buckets worst-case  $O(n^2)$  (insertion sort)
- What if we had as many buckets as the keys?
  - $n$  insertion operations
  - $n$  retrieval operations
  - $O(n)$  sorting time

# Radix sort

- In a large number of cases, we want to sort objects with multiple keys
- In such cases, we define the order of key pairs as  $(k_1, l_1) < (k_2, l_2)$  if  $k_1 < k_2$ , or  $k_1 = k_2$  and  $l_1 < l_2$
- This definition can be generalized to key tuples of any length
- This ordering is known as *lexicographic* or dictionary order
- Radix sort is the name for the technique that uses multiple stable bucket sorts for this purpose

## Summary

- Sorting is an important and well-studied computational problem
- Most sorting algorithms/applications used in practice are highly optimized, often based on multiple basic algorithms
- Naive sorting algorithms run in  $O(n^2)$  time
- Lower bound on worst-case sorting time is  $\Omega(n \log n)$ , divide-and-conquer algorithms achieve this
- Reading: Goodrich, Tamassia, and Goldwasser (2013, chapter 12)
- And a fun way to see sorting in action:  
<https://www.youtube.com/user/AlgoRythmics>

Next:

- Trees
- Reading: Goodrich, Tamassia, and Goldwasser (2013, chapter 8)

# Acknowledgments, credits, references



Goodrich, Michael T., Roberto Tamassia, and Michael H. Goldwasser (2013).  
*Data Structures and Algorithms in Python*. John Wiley & Sons, Incorporated. ISBN:  
9781118476734.







